

THE DYNAMICS OF PENDULOUS VIBRATORS

DRĂGAN Nicușor

Engineering Faculty of Brăila, "Dunărea de Jos" University from Galați
ndragan@ugal.ro, dragannicu64@yahoo.com

Keywords: dynamics, pendulous vibrator, linear modeling

Abstract: This study presents the phases of the elaboration of the calculus model and the mathematical model for one direction pendulous vibrators utilized in equipment which generate technological vibrations for civil engineering, for building materials industry, for any other technical applications. Depending on calculus hypothesis, it was determined some simplified mathematical models which point out the analytical relations between structural and dynamical parameters of the vibrating system. This writing is useful in the research work and in designing of this type of vibrators and equipment, through the calculus formula for the amplitudes of the harmonically vibrations and for the necessary power and torque of the driving motor. The one direction pendulous vibrators power-actuated by various types of rotary engines have industrial applications where the driving is made through vertical vibrations. As applications it can mention diverse process industries (building materials, pharmaceuticals, metallurgy, machine building), agriculture, civil engineering. This study analyses a calculus model of this type of vibrators and proposes a complex and unitary mathematical model, which analytically evidences the influence of structural parameters on the dynamic characteristics of vibrator-organ to work system; by solving of this model, with diverse degrees of particularization, it offers explicit calculus relations used for designing work.

Under the hypothesis of small oscillations ($\sin \theta \approx \theta$, $\cos \theta \approx 1$, $\varphi \gg \theta$), the mathematical model of steady state vibration ($\dot{\varphi} = \omega_0 = \frac{\pi n_0}{30} = \text{ct.}$, $\omega_0 t \gg \theta$) of the pendulous vibrator is

$$\begin{cases} M_t \ddot{x} - (m_1 l_1 + m_2 l) \ddot{\theta} - (m_1 l_1 + m_2 l) \dot{\theta}^2 - m_2 l_2 \omega_0^2 \cos(\omega_0 t) + b \dot{x} + kx = 0 \\ M_t \ddot{y} + (m_1 l_1 + m_2 l) \ddot{\theta} - (m_1 l_1 + m_2 l) \dot{\theta}^2 - m_2 l_2 \omega_0^2 \sin(\omega_0 t) = 0 \\ (J_1 + m_2 l^2) \ddot{\theta} - (m_1 l_1 + m_2 l) \ddot{x} + (m_1 l_1 + m_2 l) \ddot{y} - m_2 l l_2 \omega_0^2 \sin(\omega_0 t) + (m_1 l_1 + m_2 l) g \theta = -M_m \\ (-m_2 l_2 \ddot{x} + m_2 l l_2 \dot{\theta}^2 + m_2 g l_2) \sin(\omega_0 t) + (m_2 l_2 \ddot{y} + m_2 l l_2 \dot{\theta}^2) \cos(\omega_0 t) = M_m \end{cases}$$

where x and y are the displacements of the vibrator, θ is the angular displacement of the pendulum and $\varphi = \omega_0 t$ is the rotation of the unbalanced mass.

REFERENCES

- [1] Axinti, G., Drăgan, N. – "Note de curs – Mecanica teoretică. Elemente de mecanică analitică", Universitatea "Dunărea de Jos" Galați, Facultatea de Inginerie Brăila, 1994
- [2] Axinti, G., Oproescu, Gh. - "Dinamische Modellierung der einrichtungs-vibrationsgeneratoren von pendeltyp", Analele Universității "Dunărea de Jos" fascicula XIV inginerie mecanică, Galați, 1996
- [3] Axinti, G., Stoica, Gh., Axinti, A. S. - "Comportarea dinamică a generatoarelor de vibrații unidirecționale de tip pendular acționate hidraulic, utilizate pe miniutilaje de construcții", Buletinul celui de-al VI-lea Simpozion Național de Utilaje de Construcții vol. I pp. 177-183, U.T.C., Facultatea de Utilaj Tehnologic, București, 26-27 iunie 1997
- [4] Bratu, P. P. - "Vibrațiile sistemelor elastice", Editura Tehnică, București, 2000
- [5] M. Rădoi, E. Deciu - "Mecanica", Editura Didactică și Pedagogică, București, 1977